

ELECTRICAL

SOCKET EXTENSIONS / ADAPTERS / EDISON BASE RECEPTACLES

Medium Base to GU-10/GZ-10
 Porcelain Socket Adapter
 Diameter 1-5/16"
 Rated 660W – 250V
D356



Medium Base Adapter
 Porcelain Recessed Can Socket
 18" 200° Connection Leads
 Rated 660W – 250V

D287

Keyless 2-Light Offset Cluster Socket for Table Lamps
 Medium Base
 Bracket Height 3-3/8"
 1/8F x 1/8F
 24" 105° Leads
 Rated 660W – 250V
 Set Screws
D610



Medium Base (e-26) to GU-24
 High Heat Resistance Plastic Socket Adapter
 *Irreversible, Tamper Proof (Cannot Be Removed Once Installed)
 Rated 660W – 250V



***D3560**
D3561 (Non Lockable)



3-Piece Lamp holder
 Porcelain with Pull-Chain • Diameter 4-1/2"
 to fit over 3-1/4" or 4" Box • Rated 660W – 120V

D92

Standard* Pull-Chain Angle Socket
 Medium Base • Solid Brass
 Side Bushing Tapped 1/8 IPS
 Rated 250W – 250V
 Set Screw



D199 Polished

Candelabra Base (E-12) to GU-24
 High Heat Resistance Plastic Socket Adapter
 Rated 660W – 250V



D3562

Intermediate Base (E-17) to GU-24
 High Heat Resistance Plastic Socket Adapter
 Rated 660W – 250V



D3563



Fixture Receptacle
 Diameter 4-1/2" to fit over 3-1/4" or 4" Box
 Plastic • Rated 660W – 250V

D3849 (50 Pieces per Case)

Solid Unfinished 2-Light Cluster Head
 Top Cap Stud Threaded 1/4"-27
 1/8 IPS Body Thread



A611 (If 1/4F needed use Nozzle B58)

Porc Adapter GU-24 to E26
 Porcelain Socket Adapter
D3564



Fixture Receptacle
 Diameter 4-1/2" to fit over 3-1/4" or 4" Box
 Porcelain • Rated 660W – 250V

D91 (50 Pieces per Case)

Candelabra to Candelabra
 Socket Extension
D362 Extends 1/2"




Medium Base Adapter with Leads
 18" 150° Leads
 Rated 660W – 250V
D286



Porcelain Lamp holder with Pull-Chain and Outlet
 Diameter 4-1/2" to fit over 3-1/4" or 4" Box
 Rated 660W – 120V

D94

Standard vs. Electrolier



Standard (Over-Sized)

Electrolier (Modern)

*Standard is a term used to describe the original size of the metal shell lamp holder. In the early 1950's, the smaller electrolier lamp holder was introduced, and this is the size found on most all modern table & floor lamps today.

Pre-wired
clusters for easy
installation
Adjustable Up to
90° One Way



Standard*

2-Light Cluster Head
Pre-Wired with Adjustable Pull-Chain
Medium Base Sockets
1/4 IPS Body Thread (Bottom)
1/8 IPS Threaded Stem with Knurled Nut
Rated 250W – 250V

- A619** Polished & Lacquered Brass
- A620** Polished Brass Only
- A1800** Chrome Plated & Lacquered
- A1801** Antique Brass & Lacquered
- A1802** Satin Brass & Lacquered
- A1803** Satin Nickel & Lacquered



Solid Brass 2-Light "S" Arm Cluster Body
Arms Threaded 1/4"

Spread 5-1/2"
1/8 IPS Top • 1/8 IPS Bottom
A667 Unfinished
A668 Satin Brass & Lacquered

Spread 5-1/2"
1/8 IPS Top • 1/4 IPS Bottom
A662 Unfinished
A664 Satin Brass & Lacquered

Spread 7-1/2"
1/8 IPS Top • 1/4 IPS Bottom
A659 Unfinished

2-Light Adjustable Cluster Head

with Satin Brass Stem and Adjustable Shade Holder Attachment
Medium Base
Top Adjustment 4"
1/4 IP Bottom Stem 6"
Bottom Coupling 1/8 IPS



- A623** Polished Brass Center Body
- A1823** Satin Brass Center Body

Brass Plated Candelabra Base
3-Light WIRED Cluster

Top Mount Coupling 1/8 IPS
Diameter 3-3/8"
Polished Brass Plated Cups
72" SPT-1 and Ground

A652

Suggested
Bulb Size B-8



4-Hole brass plated Candle Body

Has 4 Top Holes and 1 Bottom Hole
All Slip 1/8 IPS • Diameter 2-7/8"

A648

2-Light Adjustable Cluster Head

Adjusts From 8-1/2" to 12-1/2"
7 Piece Assembly
Solid Brass Cluster Head is Unfinished
1/4 IP Satin Brass Stem
Bottom Coupling 1/8 IPS

A616



2-Light Cluster Head

Overall Height 8-1/2"
1/4 IP Satin Brass Stem
Solid Brass Cluster Head is Unfinished
Bottom Coupling 1/8 IPS

A617



Shade Holder

Attaches to the Top of a Cluster Head Socket
1/4"-27M Thread
Adjustable Height 4"
Bottom Tapped 1/8 IPS
Burnished & Lacquered

A670



2-Light "S" Arm Cluster Body

Body Diameter 2" • Spread 7"
Top Cap has Set Screw • 1/8 IPS Top Hole
1/4 IPS Bottom Hole


- A673** Brass Plated
- A674** Antique Brass



On/Off Phenolic Push Button Floor Switch

Diameter 2-1/2"
For SPT-1 and SPT-2 Wire

D337 Black



WIRING DIAGRAM



On/Off Phenolic Push Button Floor Switch

Diameter 2"
For SPT-1 and SPT-2 Wire

D338 White